

Quality Department **PRODUCT SPECIFICATION**

| SPECIALLY DENATURED ETHYL ALCOHOL SDA-40-B 190 PROOF | | | | |
|--|-------|---|-------------------|-------------|
| Test | Units | Method | Sp | ecification |
| Density in Air, Kg/L at 20 C | | Methods specified in the Revenue Canada Customs & Excise Alcoholometric Tables | 0.8106 max. | |
| Colour | | АРНА | 4 max. | |
| Miscibility with Water, at 20 C | | Visual | Complete | |
| Composition: | | | Reference Number: | 4.10-57 |
| 100 gallons ethyl alcohol 190 US proof min. | | | Approved by: | P.O. |
| 1/8 gallons tertiary butanol | | | Effective Date: | 06/Feb/2018 |
| 1/16 avoirdupois ounces of denatonium benzoate NF | | | Revision Number: | 5 |

Ethyl alcohol used in the formulation of the product:

Acids as Acetic Acid, g/100mL 0.0020 max.
Esters as Ethyl Acetate, g/100mL 0.0015 max.
Aldehydes as Acetaldehyde, g/100mL 0.0007 max.
Higher Alcohols, g/100mL 0.0040 max.
Nonvolatile Residue, g/100mL 0.0020 max.