

SAFETY DATA SHEET

1. Identification

Product identifier	Citric Acid Blender
Other means of identification	
Synonyms	Citric Blender, Citric Extract, Citric Flavor (Flavour) Base, Citric Concentrate, Citric Spirits
Recommended use	Flavoring.
Recommended restrictions	Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency (Excise) in Canada, US Tax and Trade Bureau in the US, etc.
Manufacturer/Importer/Supplier/Distributor information	
Company name	Greenfield Global Inc.
Address	6985 Financial Drive
	Missisauga, Ontario L5N 0G3

	Missisauga, Ontario Loiv 000
	Canada
Telephone	(905) 790-7500
Website	http://www.greenfield.com
Emergency phone number	CANUTEC: (613) 996-6666

2. Hazard identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2
Label elements		
	$\wedge \wedge$	
	$\sim \sim$	
Signal word	Danger	
Hazard statement	Highly flammable liquid and vapour. Causes s	serious eye irritation.
Precautionary statement		
Prevention	Keep container tightly closed. Ground and bo explosion-proof electrical/ventilating/lighting e	pen flames and other ignition sources. No smoking. nd container and receiving equipment. Use equipment. Use non-sparking tools. Take action to fter handling. Wear protective gloves/protective
Response	EYES: Rinse cautiously with water for several	I contaminated clothing. Rinse skin with water. IF IN I minutes. Remove contact lenses, if present and ersists: Get medical advice/attention. In case of fire: ry powder or water fog to extinguish.
Storage	Store in a well-ventilated place. Keep cool.	
Disposal	Dispose of contents/container in accordance	with local/regional/national/international regulations.
Other hazards	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	65 - 80
Citric acid		77-92-9	7 - 13
Other components below re	eportable levels		5 - < 7

Citric Acid Blender

Composition comments	The exact concentrations of the above listed chemicals are being withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Alberta OELs (O	ccupational Health & Safety Code, Sche	edule 1, Table 2)
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
		for Chemical Substances, Occupational Health and
Safety Regulation 296/97, Components	as amended) Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Manitoba OELs (Components	Reg. 217/2006, The Workplace Safety A	nd Health Act) Value
	Туре	
Ethanol (CAS 64-17-5)	STEL	1000 ppm
	control of Exposure to Biological or Che	
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
•	linistry of Labor - Regulation respectin	
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3 1000 ppm
	TWA ELs (Occupational Health and Safety R	1000 ppm
		1000 ppm
Canada. Saskatchewan O	ELs (Occupational Health and Safety R	1000 ppm egulations, 1996, Table 21)
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety R Type	egulations, 1996, Table 21) Value
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety R Type 15 minute	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5)	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineer	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm or the ingredient(s). naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommended
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineer	egulations, 1996, Table 21) Value 1250 ppm 1000 ppm or the ingredient(s). naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender e not been established, maintain airborne levels to an
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering strols	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched t exhaust ventilation, or other engineer exposure limits. If exposure limits hav acceptable level. Provide eyewash sta	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm or the ingredient(s). naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender ve not been established, maintain airborne levels to an ation and safety shower. ent
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering strols	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineer exposure limits. If exposure limits hav acceptable level. Provide eyewash sta	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm or the ingredient(s). naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender ve not been established, maintain airborne levels to an ation and safety shower. ent
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering strols	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched t exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash sta	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm or the ingredient(s). naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender re not been established, maintain airborne levels to an ation and safety shower. ent 6 (or goggles).
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering strols	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched t exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash sta es, such as personal protective equipme Wear safety glasses with side shields Wear appropriate chemical resistant of	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm or the ingredient(s). naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender re not been established, maintain airborne levels to an ation and safety shower. ent 6 (or goggles).
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering strols	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched t exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash sta es, such as personal protective equipme Wear safety glasses with side shields Wear appropriate chemical resistant of	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm or the ingredient(s). haust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender the not been established, maintain airborne levels below recommender the of the optimistic shower. ent f (or goggles). gloves. Suitable gloves can be recommended by the glove or penetrate the gloves. Frequent change is advisable.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering ttrols	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched t exhaust ventilation, or other engineer exposure limits. If exposure limits hav acceptable level. Provide eyewash sta es, such as personal protective equipme Wear safety glasses with side shields Wear appropriate chemical resistant of supplier. Be aware that the liquid may Wear appropriate chemical resistant of If engineering controls do not maintain limits (where applicable) or to an acce	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm or the ingredient(s). haust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender re not been established, maintain airborne levels to an ation and safety shower. ent f (or goggles). gloves. Suitable gloves can be recommended by the glove re penetrate the gloves. Frequent change is advisable.
Canada. Saskatchewan O Components Ethanol (CAS 64-17-5) logical limit values propriate engineering strols ividual protection measure Eye/face protection Skin protection Hand protection Other	ELs (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo Explosion-proof general and local exh Ventilation rates should be matched t exhaust ventilation, or other engineer exposure limits. If exposure limits hav acceptable level. Provide eyewash sta es, such as personal protective equipme Wear safety glasses with side shields Wear appropriate chemical resistant of supplier. Be aware that the liquid may Wear appropriate chemical resistant of If engineering controls do not maintain limits (where applicable) or to an acce been established), an approved respi	1000 ppm egulations, 1996, Table 21) Value 1250 ppm 1000 ppm r the ingredient(s). naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommendere not been established, maintain airborne levels to an ation and safety shower. ent a (or goggles). gloves. Suitable gloves can be recommended by the glove rependence the gloves. Frequent change is advisable. clothing. n airborne concentrations below recommended exposure eptable level (in countries where exposure limits have not rator must be worn. Respirator type: Chemical respirator work

9. Physical and chemical properties

9. Physical and chemical p	properties
Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Colorless to slight yellow.
Odour	Alcoholic.
Odour threshold	Not available.
рН	2.44
Melting point/freezing point	Not available.
Initial boiling point and boiling range	78 - 100 °C (172.4 - 212 °F)
Flash point	16 °C (60.8 °F) Tag closed cup ASTM D-56
Evaporation rate	1.8
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	3.3 (for 100% Ethanol)
Flammability limit - upper (%)	19 (for 100% Ethanol)
Vapour pressure	5.87 kPa (20 °C / 68 °F)
Vapour density	1.59
Relative density	0.85 - 0.865 (20 °C (68 °F))
Solubility(ies)	
Solubility (water)	Complete
Partition coefficient (n-octanol/water)	0.032
Auto-ignition temperature	422 °C (791.6 °F)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Dynamic viscosity	1.35 cP (20 °C (68 °F))
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Percent volatile	100 % v/v
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	No hazardous decomposition products are known.
11. Toxicological informat	ion
Information on likely routes of e	xposure

 ormation on likely routes of ex		
Inhalation	Prolonged inhalation may be harmful.	
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.	
Eye contact	Causes serious eye irritation.	
Ingestion	Expected to be a low ingestion hazard.	

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Acute toxicity	Not expected to be address toxic.		
Components	Species	Test Results	
Ethanol (CAS 64-17-5)			
Acute			
Inhalation			
Vapour			
LC50	Rat	117 - 125 mg/l, 4 Hours	
Oral			
LD50	Rat	10470 mg/kg	
Skin corrosion/irritation	Prolonged skin contact may ca	ause temporary irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitisation	'n		
Respiratory sensitisation	Not a respiratory sensitiser.		
Skin sensitisation	This product is not expected to	o cause skin sensitisation.	
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	product or any components present at greater than 0.1% are	
Carcinogenicity			
Canada - Manitoba OELs: d	arcinogenicity		
Ethanol (CAS 64-17-5)		Confirmed animal carcinogen with unknown relevance to humans.	
Reproductive toxicity	Possible reproductive hazard.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be h	narmful.	

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Citric acid (CAS 77-92-	-9)		
Aquatic			
Acute			
Crustacea	LC50	Daphnia magna	1535 mg/l, 24 hours
Fish	LC50	Carp (Leuciscus idus melanotus)	440 mg/l, 48 hours
Ethanol (CAS 64-17-5))		
Aquatic			
Acute			
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours
	EC50	Freshwater algae	275 mg/l, 72 hours
		Marine water algae	1900 mg/l
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days

Components		Species	Test Results
Chronic			
Algae	NOEC	Marine water algae	1580 mg/l
Fish	NOEC	Freshwater fish	250 mg/l
Invertebrate	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours
Other	NOEC	Lemna minor	280 mg/l, 7 days
Other			
Acute			
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours
Terrestrial			
Acute			
Plant	EC50	Terrestrial plant	633 mg/kg dw
ersistence and degradability	No data is a	vailable on the degradability of any ing	redients in the mixture.
oaccumulative potential			
Partition coefficient n-octar Citric Acid Blender	nol / water (log	3 Kow) 0.032	
Citric acid (CAS 77-92-9)		-1.64	
obility in soil	No data ava	ilable.	
her adverse effects	No data ava	ilable.	
3. Disposal consideratio	ns		
sposal instructions		reclaim or dispose in sealed containers ntainer in accordance with local/regiona	at licensed waste disposal site. Dispose of al/national/international regulations.
ocal disposal regulations	Dispose in accordance with all applicable regulations.		
azardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
aste from residues / unused oducts	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
ontaminated packaging			ue, follow label warnings even after container is pproved waste handling site for recycling or
4. Transport information			

TDG **UN number** UN1987 UN proper shipping name ALCOHOLS, N.O.S. (Ethanol) Transport hazard class(es) Class 3 Subsidiary risk -Packing group П **Environmental hazards** No. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. ΙΑΤΑ **UN number** UN1987 UN proper shipping name Alcohols, n.o.s. (Ethanol) Transport hazard class(es) Class 3 Subsidiary risk -П Packing group **Environmental hazards** No. **ERG Code** 3L Special precautions for user Read safety instructions, SDS and emergency procedures before handling. IMDG **UN number** UN1987 UN proper shipping name ALCOHOLS, N.O.S. (Ethanol)

Citric Acid Blender

Transport hazard class(es)		
Class	3	
Subsidiary risk Packing group	-	
Environmental hazards	11	
Marine pollutant	No.	
EmS	F-E, S-D	
	Read safety instructions, SDS and emergency procedures before handling.	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable. This substance/mixture is not intended to be transported in bulk.	
15. Regulatory information		
Canadian regulations	This product has been classified in accordance with the hazard criteria of the HPR and the contains all the information required by the HPR.	SDS
Controlled Drugs and Subst	ances Act	
Not regulated. Export Control List (CEPA 19	999, Schedule 3)	
Not listed.		
Greenhouse Gases		
Not listed.		
Precursor Control Regulatio	ns	
Not regulated. International regulations		
Stockholm Convention		
Not applicable.		
Rotterdam Convention		
Not applicable. Kyoto Protocol		
Not applicable. Montreal Protocol		
Not applicable. Basel Convention		
Not applicable.		
International Inventories		
Country(s) or region	Inventory name On inventory ()	/es/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).		

16. Other information

Revision date Version No. Disclaimer 26-May-2021

02

This product is subject to Greenfield Global Inc.'s terms and conditions, which can be found at http://www.greenfield.com/tc-po-can/. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the time of writing.