# SAFETY DATA SHEET



#### 1. Identification

Product identifier SIS SIH 200 Proof

Other means of identification None.

Recommended use General purpose solvent.

**Recommended restrictions**Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company Name Greenfield Global USA Inc.
Address 1101 Isaac Shelby Drive
Shelbyville, KY 40065

USA

 Telephone
 502.232.7600

 Fax
 502.633.6100

Company Name Greenfield Global USA Inc.

Address 58 Vale Road

Brookfield, CT 06804

USA

 Telephone
 203.740.3471

 Fax
 203.740.3481

**Emergency phone number** 

USA CHEMTREC: 1.800.424.9300 (CCN 17213)
International CHEMTREC: +1.703.527.3887 (CCN 17213)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 1 (central nervous system, optic

nerve)

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. Causes damage to organs

(central nervous system, optic nerve).

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling.

measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Wear protective gloves/eye protection/face protection.

**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed: Call a poison

center/doctor. In case of fire: Use appropriate media to extinguish.

**Storage** Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Ingestion

Chemical name	CAS number	%
Ethyl alcohol	64-17-5	47.2 - 48.2
Propan-2-ol	67-63-0	49.5 - 50.5
Methanol	67-56-1	2.1 - 2.6

**Composition comments** 

All concentrations are in percent by weight unless otherwise indicated.

#### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a

one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Methanol: Human exposure to methanol may result in illness, systemic poisoning, blindness, optic nerve damage and perhaps death, after being ingested, absorbed through the skin or inhaled. Death due to cardiac or respiratory failure has been reported in some cases from consumption of as little as 30 mls.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.

Use standard firefighting procedures and consider the hazards of other involved materials.

SIS SIH 200 Proof SDS US 945118 Version #: 01 Revision date: - Issue date: 27-September-2018 2 / 10

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is completely soluble in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

**Environmental precautions** 

# 7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1000)
Components	Typo

Components	туре	value	
Ethyl alcohol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
Methanol (CAS 67-56-1)	PEL	260 mg/m3	
		200 ppm	
Propan-2-ol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
US. ACGIH Threshold Limit Values	<b>;</b>		
Components	Туре	Value	
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm	
Methanol (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Ethyl alcohol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	

SIS SIH 200 Proof SDS US

945118 Version #: 01 Revision date: - Issue date: 27-September-2018

US. NIOSH: Pocket Guide to Chemical Hazard	US.	. NIOSH:	<b>Pocket</b>	Guide 1	to	Chemical	Hazard	s
--	-----	----------	---------------	---------	----	----------	--------	---

Components	Туре	Value	
Methanol (CAS 67-56-1)	STEL	325 mg/m3	
		250 ppm	
	TWA	260 mg/m3	
		200 ppm	
Propan-2-ol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	

#### **Biological limit values**

Methanol (CAS 67-56-1)         15 mg/l         Methanol         Urine         *           Propan-2-ol (CAS 67-63-0)         40 mg/l         Acetone         Urine         *	Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol (CAS 67-63-0) 40 mg/l Acetone Urine *	Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
	Propan-2-ol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1) Skin designation applies.

**US - Tennessee OELs: Skin designation** 

Methanol (CAS 67-56-1) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

**US. NIOSH: Pocket Guide to Chemical Hazards** 

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

# Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical goggles are recommended.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn. Respirator type: Chemical respirator with

organic vapor cartridge.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

#### **Appearance**

considerations

Physical state Liquid.
Form Liquid.
Color Colorless.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -173.2 °F (-114 °C)

Initial boiling point and boiling 176 °F (80 °C)

range

**Flash point** 55.4 - 60.8 °F (13.0 - 16.0 °C) Closed Cup

19 % v/v

**Evaporation rate** Expected to be rapid.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower 3.3 % v/v

(%)

Flammability limit - upper

(%)

Vapor pressure44.6 mm HgVapor density1.6 (air = 1)Relative densityNot available.

Solubility(ies)

**Solubility (water)** Completely soluble.

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperature 685.4 °F (363 °C)

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsAcids. Strong oxidizing agents. Chlorine. Isocyanates.Hazardous decompositionNo hazardous decomposition products are known.

products

#### 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Prolonged skin contact may cause temporary irritation. May be absorbed through the skin.

**Eye contact** Causes serious eye irritation. **Ingestion** May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Coughing.

Methanol: Human exposure to methanol may result in illness, systemic poisoning, blindness, optic nerve damage and perhaps death, after being ingested, absorbed through the skin or inhaled. Death due to cardiac or respiratory failure has been reported in some cases from consumption of as little as 30 mls.

#### Information on toxicological effects

Acute toxicity May be harmful if swallowed.

Components **Species Test Results** Ethyl alcohol (CAS 64-17-5) **Acute** Inhalation Vapor Rat LC50 117 - 125 mg/l, 4 Hours Oral Rat LD50 10470 mg/kg Propan-2-ol (CAS 67-63-0) **Acute Dermal** LD50 Rabbit 12870 mg/kg Inhalation Vapor LC50 Rat 72.6 mg/l, 4 hours Oral LD50 Rat 4710 mg/kg Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Propan-2-ol (CAS 67-63-0) 3 Not classifiable as to carcinogenicity to humans.

**NTP Report on Carcinogens** 

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Causes damage to organs (central nervous system, optic nerve).

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

#### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

	Species	Test Results
17-5)		
EC10	Freshwater algae	11.5 mg/l, 72 hours
EC50	Freshwater algae	275 mg/l, 72 hours
	Marine water algae	1900 mg/l
NOEC	Marine water algae	1580 mg/l
LC50	Freshwater fish	11200 mg/l, 24 hours
NOEC	Freshwater fish	250 mg/l
	EC10 EC50 NOEC LC50	EC10 Freshwater algae EC50 Freshwater algae Marine water algae NOEC Marine water algae LC50 Freshwater fish

Components		Species	Test Results
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
	NOEC	Lemna minor	280 mg/l, 7 days
Other			
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours
Terrestial			
Plant	EC50	Terrestrial plant	633 mg/kg dw
Methanol (CAS 67-56-1)			
Aquatic			
Acute			
Crustacea	EC50	Daphnia magna	> 10000 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	15400 mg/l, 96 hours
Propan-2-ol (CAS 67-63-	0)		
Aquatic			
Acute			
Crustacea	LC50	Daphnia magna	> 10000 mg/l, 24 hours
Fish	LC50	Pimephales promelas	9640 mg/l, 96 hours
Chronic			
Crustacea	EC50	Daphnia magna	> 100 mg/l, 21 days
	NOEC	Daphnia magna	141 mg/l, 16 days
			30 mg/l, 21 days

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available for this product.

Partition coefficient n-octanol / water (log Kow)

Methanol (CAS 67-56-1) -0.77Propan-2-ol (CAS 67-63-0) 0.05

Mobility in soil

The product is completely soluble in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions** 

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport information

DOT

UN1987 **UN** number Alcohols, n.o.s. UN proper shipping name

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) Ш Packing group

**Environmental hazards** 

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 172, IB2, T7, TP1, TP8, TP28

4b, 150 Packaging exceptions Packaging non bulk 202 Packaging bulk 242

IATA

**UN** number UN1987 **UN** proper shipping name Alcohols, n.o.s.

Transport hazard class(es)

Class 3 Subsidiary risk Packing group Ш **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

UN1987 **UN** number

**UN** proper shipping name ALCOHOLS, N.O.S.

Transport hazard class(es)

Class 3 Subsidiary risk П Packing group **Environmental hazards** 

Marine pollutant No. **EmS** F-E. S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Methanol (CAS 67-56-1) Listed. Propan-2-ol (CAS 67-63-0) Listed.

Not established.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SDS US SIS SIH 200 Proof

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methanol	67-56-1	2.1 - 2.6
Propan-2-ol	67-63-0	49.5 - 50.5

#### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

# FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethyl alcohol (CAS 64-17-5)

Propan-2-ol (CAS 67-63-0)

Low priority

Low priority

#### **US** state regulations

#### **US. Massachusetts RTK - Substance List**

Ethyl alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propan-2-ol (CAS 67-63-0)

#### US. New Jersey Worker and Community Right-to-Know Act

Ethyl alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propan-2-ol (CAS 67-63-0)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propan-2-ol (CAS 67-63-0)

#### US. Rhode Island RTK

Ethyl alcohol (CAS 64-17-5) Methanol (CAS 67-56-1) Propan-2-ol (CAS 67-63-0)

#### California Proposition 65



**WARNING:** This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

# California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Methanol (CAS 67-56-1) Propan-2-ol (CAS 67-63-0)

# **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Country(s) or region Inventory name On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date 27-September-2018

Revision date - 01

HMIS® ratings Health: 4

Flammability: 3 Physical hazard: 0

**Disclaimer** This product is subject to Greenfield Global USA Inc.'s terms and conditions, which can be found

at http://www.greenfield.com/tc-po-us/. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the

time of writing.

SIS SIH 200 Proof SDS US

945118 Version #: 01 Revision date: - Issue date: 27-September-2018